



Fire Control for the 21st Century

US Army TACOM
Armament Research Development and Engineering Center
Fire Support Armaments Center
Fire Control and Life Cycle Software Engineering Division
Picatinny Arsenal, New Jersey



Beyond

"Classic" individual system fire control

TO

Fire control for the battlefield group



Descript ion/ Definition

A framework of linked fire control elements on distributed battlefield platforms that act in concert with one another to provide enhanced firing solution computation and efficient application of firepower assets to the engagement of individual and multiple targets.




Is Not:

- A command and control system
- > A communications system
- > B2C2 / CVCC / IVIS / FBCB2 / Appliqué
- A planning or logistics status assessment tool
- > A graphical display terminal or other crew interactive device

<u>But:</u>

Must appropriately interface with these items in order to function





Concept Features/ Characteristics

Filters data to extract needed information

Uses calculated P{H} values for target assignments to each firing platform in a group

Dynamic REAL-TIME tactical firing assignments and adjustments throughout the battle, running continuously in background



SAMPLE DATA ELEMENTS

TARGET STATE

- LOCATION
- SPEED
- DIRECTION
- THREAT VALUE
- PREDICTED LOCATION

NON-STANDARD CONDITIONS

- CROSSWIND / RANGEWIND
- AIR TEMP / AIR DENSITY
- PROPELLANT GRAIN TEMP


FIRING PLATFORM STATE

- READINESS
- LOCATION
- SPEED
- DIRECTION
- PITCH / CANT
- TURRET / HULL RELATION
- READY ROUND TYPE
- MUZZLE POSITION

TERRAIN DATA

- ELEVATION
- CONTOURS
- LOS RESTRICTIONS

Software Modules and Functions



DIFM OPERATION

Target Types
Target Locations
Target States

Follower States Ready Ammo Follower Locations DIFM SOFTWARE

Follower Availability
Terrain Intervention
Target Prioritization
Group P(H) Determination
Target State Estimation

Position
Emplacement
and
Search Sector
Assignments

Target to Shooter Assignments

Semi-Automatic Weapon Pointing

LOCAL AREA COMMO

Target Data from Observers Shooter Assignment

DIFM OPERATIONAL INTERFACES

CREW INTERFACES

Touch Screen, Switches,
Displays and Electro-Optics

WEAPON PLATFORM INTERFACES

Sensor and Weapon Control

LONG HAUL COMMO

Targets Assigned or Entering Sector

DIFM SOFTWARE MODULE

OWN VEHICLE STATE DATA



Payof f

Uses platform and target state data to compute hit probabilities for all elements in unit Optimizes shooter / target pairings

Mitigates overkill or underkill

and conserves ammunition

during multiple target engagements

Improves target state estimation through maximum use of available multiple platform sensors

Reduces the incidence of fratricide through multiple vantage point target data and observation before firing

Improves target servicing rates Rapid reaction **Increases Optempo**



STATUS / TECH OBJECTIVES

- PART OF THE MULTI-ROLE ETC ARMAMENTS STO FOR FCS
- DEVELOP THE MULTI-SHOOTER ALGORITHM
- SIMULATE THE SOFTWARE FUNCTION AND BATTLEFIELD OPERATION
- MEASURE PERFORMANCE IN TERMS OF TECHNICAL EXIT CRITERIA



Increase

Target Hits per Stowed Ammunition Load Target Kills per Stowed Ammunition Load Target Servicing Rate (Optempo)

Decrease

Time to Complete Assigned Mission (Optempo)
Ammunition Consumption per Mission
Friendly Mortality Rate
Fratricide Rate



POINTS OF CONTACT

US Army TACOM-ARDEC
Fire Support Armaments Center
Fire Control and Life Cycle Engineering Division
Attn: AMSTA-AR-FSF-D
Picatinny Arsenal, NJ 07806-5000

Clifford W. Langan

DPO, Combat Vehicle Fire Control Devel.

DSN 880-6028

Comm. (973) 724-6028

Email: clangan@pica.army.mil

Tony DiGiacomo

Systems Engineer

DSN 880-6926

Comm. (973) 724-6926

Email: rdigiac@pica.army.mil